

FOLDING TRAILER INSTALLATION INSTRUCTIONS

PREPARING FOR INSTALLATION

Make sure you've purchased the correct size cover for your RV by visiting [Covercraft.com/c/rv](https://www.covercraft.com/c/rv) to review sizing information. Measure your RV from end to end, including bumpers, spare tire, and ladder, but excluding the hitch (if applicable) and any mirrors that extend beyond the front of the coach. If you are unsure about sizing, call Covercraft at **800-541-2326** to speak with a customer service representative.

Clean your RV thoroughly before covering it; a dirty surface can result in black streaks. Also, pad all sharp edges on the RV, including rain gutters (use the included rain gutter covers), steps, ladder (use the included ladder cap), and any abrasive corners. The cover may shift in the wind and could tear if sharp edges are not properly padded. Please note that Covercraft does not offer warranty coverage against wind damage. (You'll want to cover the ladder cap last so it remains usable during installation.)

Important: Installation does not require climbing onto the roof. A step ladder may be used. However, if you can safely walk on your RV's roof, installation will be much faster.

INSTALLATION STEPS

1. Identify the Front of the Cover

- Locate the front side of the trailer cover to ensure proper placement.

2. Position the Cover Over the Trailer

- Pull the sides of the cover down, draping them evenly over your trailer.

3. Secure the Front Grommets

- Use the included cord to thread through the front grommets.
- Tighten the cord securely and tie it off to hold the cover in place.

4. Secure the Rear Grommets

- Thread the cord through the rear grommets.
- Tighten and tie off to ensure the cover is firmly attached.

5. Unroll the Trailer Cover

- Lay the trailer cover adjacent to your trailer.
- Fully unwind all straps and buckles to prepare for installation.

FOLDING THE TRAILER COVER

6. Attach Straps and Buckles for a Snug Fit

- Connect the straps and buckles from one side of the trailer to the other.
- Tighten them to ensure the cover fits snugly, preventing movement and ensuring maximum protection.